## PATENT ABSTRACTS OF JAPAN

(11)Publication number:

2002-169478

(43) Date of publication of application: 14.06.2002

(51)Int.CI.

G09F 9/00 5/08 GO2B

GO2B 5/10 GO2F 1/13357 G09F 13/04

(21)Application number: 2000-362759

(71)Applicant: MATSUI KOICHI

(22)Date of filing:

29.11.2000


(72)Inventor: MATSUI KOICHI

## (54) DIRECTLY UNDER TYPE ILLUMINATOR

## (57)Abstract:

PROBLEM TO BE SOLVED: To secure the productivity of a light reflector of high brilliance and high homogeneity by facilitating the settings of the reflective unit of each light source in the light reflector of a directly under type illuminator.

SOLUTION: The reflective unit 4 of each light source 2 of a light reflector 3 is constituted by intermediate reflection planes 5 at both sides of the light source 2, and curved light reflectors 6 at both ends. The central positions P1 and P2 of the circular arc of each curved light reflector 6 are displaced to a reflective unit 4 side adjacent from the directly under position of the center of the light source 2, respectively, and the adjacent curvature reflection plane 6 have the cross-sectional shape in the upper end intersection of a circular arc with a different center 2. Thereby, reflected light is prevented from deeply entering into the adjacent reflective unit 4 side while turning reflected light to the light source 2 side, and from influencing the settings of each reflective unit 4.



## **LEGAL STATUS**

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision

of rejection]
[Date of requesting appeal against examiner's decision of rejection]
[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office